

Advies voor de installatie van vloerbedekkingen op VarioKomp – Vloerverwarming, 20 mm

Nieuwe vloerbedekking	Textile vloerbedekking	Naaldvilt	Linoleum	PVC, CV-PVC-Design	Meerlaagsparket
Lijm*	WAKOL D 3304 WAKOL D 3306 WAKOL D 3308 WAKOL D 3310 WAKOL D 3311 WAKOL D 3312 WAKOL D 3360 WAKOL D 3240	WAKOL D 3304 WAKOL D 3308 WAKOL D 3310 WAKOL D 3311 WAKOL D 3312 WAKOL D 3360 WAKOL D 3240 WAKOL MS 550	WAKOL D 3304 WAKOL D 3311 WAKOL D 3318 WAKOL D 3360 WAKOL D 3240 WAKOL MS 550	WAKOL D 3307 WAKOL D 3317 WAKOL D 3318 WAKOL D 3319 WAKOL D 3320 WAKOL D 3360 WAKOL MS 550 WAKOL MS 552	WAKOL MS 228 WAKOL MS 230 WAKOL MS 232 WAKOL MS 260 WAKOL MS 262 WAKOL MS 290 WAKOL MS 292
Egaliseren* (indien nodig)	WAKOL A 830 Egaliseermiddel in 3-5 mm laagdikte				
Voorstrijken* (indien nodig)	WAKOL D 3040 Voorstrijkconcentraat, 1:2 met water verdund				
Vorbereiden	Stofzuigen				
Ondergrond	Variotherm Vloerverwarming Droogbouw 20 mm, VarioKomp Volgens de voorschriften en gebruiksaanwijzing van de fabrikant geïnstalleerd, afgevuld met de speciale Kompakt vulmassa				

*EC1 PLUS volgens Emicode-classificatie volgens de criteria van de GEV. Details over deze classificering kunt u op onze website vinden.

De verschillende, ons niet vooraf bekend zijnde concrete omstandigheden van het project, sluiten aansprakelijkheid van deze adviezen uit. Daarom adviseren wij zelf eerst voldoende eigen tests uit te voeren. De op dat moment geldende regels in branche, de op dat moment geldende normen en merkbladen en de leginstructies van de fabrikant van de vloerbedekking, moeten worden aangehouden. S.v.p. onze verwerkingsinstructies uit de technische merkbladen van de specifieke producten in acht nemen. Graag staan wij u met onze adviezen voor specifieke projecten ter beschikking.

Met het verschijnen van dit advies verliezen alle vorige versies hun geldigheid

Wakol GmbH, Anwendungstechnik, Bottenbacher Str. 30, 66954 Pirmasens. Tel.: +49 (0) 6331 8001-187. Fax: +49 (0) 6331 8001-852. www.wakol.com
 Voor Nederland en België: Lecol, Schutweg 6, 5145 NP Waalwijk Tel: 0416 566540 www.lecol.nl

Installation recommendation for laying floorings on VarioKomp - underfloor heating, 20 mm

new flooring	textile flooring	needle fleece flooring	linoleum	PVC-, CV-flooring LVT flooring	multi-layer parquet
adhesive*	WAKOL D 3304 WAKOL D 3306 WAKOL D 3308 WAKOL D 3310 WAKOL D 3311 WAKOL D 3312 WAKOL D 3360 WAKOL D 3240	WAKOL D 3304 WAKOL D 3308 WAKOL D 3310 WAKOL D 3311 WAKOL D 3312 WAKOL D 3360 WAKOL D 3240 WAKOL MS 550	WAKOL D 3304 WAKOL D 3311 WAKOL D 3318 WAKOL D 3360 WAKOL D 3240 WAKOL MS 550	WAKOL D 3307 WAKOL D 3317 WAKOL D 3318 WAKOL D 3319 WAKOL D 3320 WAKOL D 3360 WAKOL MS 550 WAKOL MS 552	WAKOL MS 228 WAKOL MS 230 WAKOL MS 232 WAKOL MS 260 WAKOL MS 262 WAKOL MS 290 WAKOL MS 292
levelling* (if necessary)	WAKOL A 830 Levelling Compound in 3-5 mm layer thickness				
primer* (if necessary)	WAKOL D 3040 Primer Concentrate, approx. 50 g concentrate /m ² 1:2 diluted				
preparatory work	Vacuum cleaning				
subfloor	Variotherm modular floor heating dryboard 20 mm, VarioKomp According on the manufacturer instructions installed, filled with compact filler				

* EC1 PLUS according to Emicode classification and according to GEV. For details on the differentiation, please refer to our homepage.

The different, specific construction site conditions not known to us in advance exclude any claim from this information. We therefore recommend that you conduct your own tests. The recognized rules of profession, the currently applicable standards, information sheets and the laying instructions of the flooring manufacturer must be observed. Please note our technical information of the individual products. We are happy to answer any questions, likewise to advise construction details and recommendations. With the publication of this recommendation, all previous versions become invalid.

Wakol GmbH, technical service, Bottenbacher Str. 30, 66954 Pirmasens. Phone.: +49 (0) 6331 8001-187. Fax: +49 (0) 6331 8001-852. www.wakol.com

15.04.2020